

CONFIGURATION AND MONITORING ASSISTANT

PRODUCT OVERVIEW



NGC-CMA2-ZONE1



NGC-CMA2-ZONE2

The nVent RAYCHEM NGC-CMA2 is an easy-to-use wireless tablet for configuration and monitoring of nVent RAYCHEM NGC-20 control units. The tablet has an intuitive user interface eliminating the need for extensive training. The tablet is available in two versions: For Zone 2 (Zone 22) use the NGC-CMA2-ZONE2. For Zone 1 (Zone 21) use the NGC-CMA2-ZONE1.

HARDWARE DESIGN

The NGC-CMA2 devices are designed for high productivity in an industrial environment. They are protected against humidity, dust, corrosion and extreme ambient temperatures. The tablet has an 8" TFT display.

SOFTWARE

The NGC-CMA2 software is designed to provide full configuration and monitoring capabilities of the NGC-20 control units. The NGC-CMA2 allows wireless connectivity via Bluetooth® to any NGC-20 unit within range. The devices are based on Samsung technology and are running Android operating system.

GENERAL	RAYCHEM NGC-CMA2-ZONE2	RAYCHEM NGC-CMA2-ZONE1
Typical use	NGC-CMA2 units are used for the configuration and monitoring of NGC-20 of heat-tracing control units.	
Approvals/Certification	EPS 15 ATEX 1 793 X Ex II 3G Ex ic IIC T5 Gc IECEx EPS 15.0003X Ex ic IIC T5 Gc	Sira 15ATEX1205X Ex II 2GD Ex db ia op is IIC T5 Gb Ex tb IIIC T100°C Db Ta = -20°C to +50°C IECEx SIR 15.0075X Ex db ia op is IIC T5 Gb Ex tb IIIC T100°C Db Ta = -20°C to +50°C
EAC	In progress	In progress
Conditions	Refer to Hazardous Area Certification	Refer to Hazardous Area Certification
Environmental protection	IP67	IP64
Compatible control units	Raychem NGC-20-C-E and NGC-20-CL-E	
Operating Temperature	-20°C to +55°C	-20°C to +50°C

GENERAL	RAYCHEM NGC-CMA2-ZONE2	RAYCHEM NGC-CMA2-ZONE1
Dimensions	131,1 x 225,1 x 13,6 mm (incl. protective case)	162,1 x 256,0 x 33,3 mm (without stylus holder) 162,1 x 271,9 x 33,3 mm (with stylus holder)
Connectivity	Bluetooth, WiFi and USB connector	Bluetooth, WiFi and USB connector
Operating system	Android O.S.	Android O.S.
Processor	Quad core 1.2 GHz	Quad core 1.2 GHz
Bluetooth interface	Bluetooth SmartReady LE 4.0	Bluetooth SmartReady LE 4.0
Memory	RAM 1.5 GB, ROM 16GB with microSD up to 64 GB	RAM 1.5 GB, ROM 16GB with microSD up to 64 GB
Wireless LNA	WiFi 802.11 a/b/g/n	WiFi 802.11 a/b/g/n
Display	8" TFT with 1280 x 800 pixels	8" TFT with 1280 x 800 pixels
Charger	EU, UK, US and AU compatible	EU, UK, US and AU compatible
Software (included)	General Android apps	General Android apps
Keyboards & buttons	Touchscreen, buttons on the side	Touchscreen, buttons on the side
Captive pen	included	included

ORDERING INFORMATION AND WEIGHT	NGC-CMA2-ZONE2	NGC-CMA2-ZONE1
Part Number	1244-018987	1244-018988
Weight	562 g	1250 g

Europe, Middle East, Africa

Tel: +32.16.213.511
Fax: +32.16.213.603
thermal.info@nvent.com

United Kingdom

Tel: 0800 969 013
Fax: 0800 968 6241
salesthermaluk@nvent.com

Ireland

Tel: 1800 654 241
Fax: 1800 654 240
salesie@nvent.com



[nVent.com](https://www.nvent.com)

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2018 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

Raychem-DS-EU0842-NGCCMA2-EN-1805